




Series 2510



Low Pressure Capsule Gauges

Brass wetted parts

Stainless steel case and bayonet ring

Re-calibration screw on dial

Case size 2 1/2" & 4"

ENFM low pressure gauges utilize a diaphragm capsule which is very sensitive for measuring low pressures and vacuum. These gauges can be used with gases that are not corrosive to bronze and brass.

Standard gauge specifications

Case:	Stainless steel AISI 304
Bezel:	Bayonet stainless steel AISI 304
Dial:	White aluminum with black and blue scales and adjustment screw to re-zero the pointer
Pointer:	Black aluminum
Window:	Transparent acrylic
Capsule:	Bronze
Connection:	Brass
Movement:	Brass
Accuracy:	1.6 % of span

Series	2511	2511	2514	2514
Case Size	2 1/2"	4"	2 1/2"	4"
Connection Size	1/4" NPT	1/4" NPT	1/4" NPT	1/4" NPT
Article number	DD136A3E	DD136A5E	DD136C3E	DD136C5E
Pressure Ranges				
0-15" H ₂ O/mm	152kf	152kf	152kf	152kf
0-30" H ₂ O/mm	155kf	155kf	155kf	155kf
0-60" H ₂ O/mm	158kf	158kf	158kf	158kf
0-100" H ₂ O/mm	160kf	160kf	160kf	160kf
0-160" H ₂ O/mm	162kf	162kf	162kf	162kf
0-200" H ₂ O/mm	163kf	163kf	163kf	163kf
0-15" H ₂ O/Kpa	152kj	152kj	152kj	152kj
0-30" H ₂ O/Kpa	155kj	155kj	155kj	155kj
0-60" H ₂ O/Kpa	158kj	158kj	158kj	158kj
0-100" H ₂ O/Kpa	160kj	160kj	160kj	160kj
0-160" H ₂ O/Kpa	162kj	162kj	162kj	162kj
0-200" H ₂ O/Kpa	163kj	163kj	163kj	163kj
0-20 oz./H ₂ O	155kk	155kk	155kk	155kk
0-32 oz./H ₂ O	157kk	157kk	157kk	157kk
0-60 oz./H ₂ O	160kk	160kk	160kk	160kk
0-3 psi	159kb	159kb	159kb	159kb
0-5 psi	161kb	161kb	161kb	161kb
Vacuum ranges				
-15-0"/H ₂ O/mm	102kf	102kf	102kf	102kf
-30-0"/H ₂ O/mm	105kf	105kf	105kf	105kf
-60-0"/H ₂ O/mm	108kf	108kf	108kf	108kf
-100-0"/H ₂ O/mm	110kf	110kf	110kf	110kf
-160-0"/H ₂ O/mm	112kf	112kf	112kf	112kf
Mounting Options				
Backflange 2512	DD136B3E	DD136B5E		
Frontflange 2516			DD136D3E	DD136D5E
U clamp 2517			DD136F3E	

Items shown in bold are normally stocked items

To order, add pressure range code after article number, example: **DD136A3E152kf**